

CR-171 742
C-1


(NASA-CR-171742) SPACE SHUTTLE ICE
SUPPRESSION SYSTEM VALIDATION, VOLUME 3
Final Report (Texas A&M Univ.) 171 p
HC A08/1 A01

N84-17246

CSCI 22B

Unclass

G3/16 18331



TEXAS ENGINEERING EXPERIMENT STATION

The Texas A&M University System

College Station, Texas 77843

SPACE SHUTTLE ICE SUPPRESSION
SYSTEM VALIDATION
TEES-TR-4587-82-01
VOLUME III

J.L.F. PORTEIRO, D.J. NORTON
AEROSPACE ENGINEERING DEPARTMENT
AND
T.C. POLLOCK
ENGINEERING DESIGN AND GRAPHICS DEPARTMENT

Prepared for
NASA Lyndon B. Johnson Space Center
Thermal Technology Branch
Houston, Texas 77058
Under Contract NAS 9-16443

Prepared by
Texas Engineering Experiment Station
Texas A&M University
College Station, Texas 77843

PRESSURE DATA


(4)

NOMINAL CONFIGURATION
GROUP I
INFLUENCE OF NOZZLE SIZE, NO WIND
RUNS 11, 12.1 and 13



$P = 32 \text{ psia}$

$V = 0 \text{ KNOTS}$




$\phi = 0^\circ$





ORIGINAL PAGE IS
OF POOR QUALITY



ORIGINAL PAGE IS
OF POOR QUALITY



ORIGINAL PAGE 10
OF POOR QUALITY



NOMINAL CONFIGURATION
GROUP II
INFLUENCE OF NOZZLE SIZE ON WIND PENETRATION
RUNS 7, 9.1, 5 and 8




$P = 32 \text{ psia}$

$V = 20 \text{ KNOTS}$

$\beta = 338^\circ$





$\phi = -30^\circ$

ORIGINAL QUALITY
OF POOR QUALITY






$\theta = 40$ to 45
 □-RUN 7, NO NOZZLE FLOW ○-RUN 9 (11), SMALL △-RUN 11, NOMINAL
 ×-RUN 10, LARGE

ORIGINAL PAGE 19
OF FOUR QUALITY



ORIGINAL PAGE IS
OF POOR QUALITY



□ - RUN7, NO NOZZLE FLOW ○ - RUN9 (1), SMALL △ - RUN8, NOMINAL
x - RUN8, LARGE

NOMINAL CONFIGURATION

GROUP III

INFLUENCE OF NOZZLE PRESSURE ON WIND PENETRATION

RUNS 6.1, 6.2 and 6.3





$V = 30$ KNOTS

$\beta = 336^\circ$




$\phi = 0^\circ$




Nominal Nozzles

ORIGINAL PAGE IS
OF POOR QUALITY



ORIGINAL PAGE 13
OF POOR QUALITY





□-RUN 6(11)-P=32 psia ○-RUN 6(2)-P=27 psia △-RUN 6(3)-P=26 psia

ORIGINAL PAGE IS
OF POOR QUALITY

NOMINAL CONFIGURATION

GROUP IV

WIND VELOCITY EFFECTS AT 338°

RUNS 12.1, 3, 1 and 2





$$P = 32 \text{ psia}$$

$$\beta = 338^\circ$$




$$\phi = 0^\circ$$



Nominal Nozzles

ORIGINAL PAGE 19
OF POOR QUALITY



ORIGINAL PAGE 13
OF POOR QUALITY





ORIGINAL COPY
OF POOR QUALITY

NOMINAL CONFIGURATION

GROUP V

NOZZLE PRESSURE EFFECTS, NO WIND




RUNS 12.1, 12.2 and 12.3


$V = 0$ KNOTS

$\phi = 0^\circ$



Nominal Nozzles


ORIGINAL PAGE 17
OF POOR QUALITY







ORIGINAL FIGURE
OF POOR QUALITY





ORIENTATION
OF POOR QUALITY



□-RUN12(1), P=32 psia ○-RUN12(2), P=27 psia △-RUN12(3), P=26 psia



NOMINAL CONFIGURATION

GROUP VI

WIND VELOCITY EFFECTS AT 112°

RUNS 12.1, 17.1, 17.2, 17.3 and 17.4




$$P = 32 \text{ psia}$$

$$\beta = 112^\circ$$




$$\phi = 0^\circ$$

Nominal Nozzles




ORIGINAL PAGE IS
OF POOR QUALITY



ORIGINAL PAGE IS
OF POOR QUALITY



ORIGINAL PAGE IS
OF POOR QUALITY



\square -RUN12(1), V=0 KTS \circ -RUN17(1), V=20 KTS P=0 psia Δ -RUN17(3), V=30 KTS
 \times -RUN17(2), V=20 KTS $+$ -RUN17(4), V=10 KTS



NOMINAL CONFIGURATION

GROUP VII

NOMINAL VELOCITY EFFECTS AT 202°

RUNS 12.1, 14, 16.1, 15 and 16.2




$$P = 32 \text{ psia}$$

$$\beta = 202^\circ$$




$$\phi = 0^\circ$$

Nominal Nozzles




ORIGINAL PAGE IS
OF POOR QUALITY



ORIGINAL PAGE 19
OF POOR QUALITY



ORIGINAL PAGE 13
OF POOR QUALITY



\square - RUN 12(1), V=0 KTS \circ - RUN 14, V=20 KTS P=0 Δ - RUN 16(1), V=30 KTS
 \times - RUN 15, V=20 KTS + - RUN 16(2), V=10 KTS





NOMINAL CONFIGURATION
GROUP VIII
WIND VELOCITY EFFECTS ON WIND PENETRATION
RUNS 5 and 6.1

$P = 32 \text{ psia}$




$\beta = 338^\circ$




$\phi = -30^\circ$

Nominal Nozzles



ORIGINAL PAGE IS
OF POOR QUALITY





□-RUN5, V=20 KTS ○-RUN6(1), V=30 KTS

NOMINAL CONFIGURATION

GROUP IX

NOZZLE AZIMUTH ANGLE EFFECTS

RUNS 1.1, 4 and 5




P = 32 psia




V = 20 KNOTS

$\beta = 338^\circ$




Nominal Nozzles

ORIGINAL PAGE 13
OF POOR QUALITY





ORIGINAL PAGE IS
OF POOR QUALITY



□-RUN1, $\theta=0$ ○-RUN4, $\theta=-15$ Δ-Run5, $\theta=-30$

VARIABLE NOZZLE SIZE CONFIGURATION

GROUP X

NOZZLE PRESSURE EFFECTS




RUNS 28.1, 28.2 and 28.3




$V = 20$ KNOTS




$\beta = 338^\circ$

$\phi = 0$

ORIGINAL PAGE IS
OF POOR QUALITY







□-RUN28(1), P=32 psia ○-RUN28(2), P=27 psia △-RUN28(3), P=20 psia

ORIGINAL PAGE IS
OF POOR QUALITY

VARIABLE NOZZLE SIZE CONFIGURATION

GROUP XI




NOZZLE AZIMUTH ANGLE EFFECTS




RUNS 28.1, 29.1 and 30.1

$P = 32 \text{ psia}$



$V = 20 \text{ KNOTS}$

$\beta = 338^\circ$





ORIGINAL BACK IS
OF POOR QUALITY









VARIABLE NOZZLE SIZE CONFIGURATION
GROUP XII
INFLUENCE OF NOZZLE PRESSURE ON WIND PENETRATION
FOR A -15° NOZZLE AZIMUTH ANGLE
RUNS 29.1, 29.2 and 29.3



$V = 20$ KNOTS

$\beta = 338^\circ$

$\phi = -15^\circ$







ORIGINAL PAGE IS
OF POOR QUALITY







VARIABLE NOZZLE SIZE CONFIGURATION
GROUP XIII
INFLUENCE OF NOZZLE PRESSURE ON WIND PENETRATION
FOR A -30° NOZZLE AZIMUTH ANGLE
RUNS 30.1, 30.2 and 30.3




$V = 20$ KNOTS



$\beta = 338^\circ$

$\phi = -30^\circ$









MARSHALL SPACE FLIGHT CENTER CONFIGURATION





GROUP XIV




WIND VELOCITY EFFECTS AT 0°, LOW FLOWRATE




RUNS 33.1 and 33.2

$\beta = 0^\circ$

Low Flowrate







□-RUN32(2), V=0 KTS ○-RUN33(1), V=7 KTS △-RUN33(2), V=20 KTS

ORIGINAL PAGE IS
OF POOR QUALITY

MARSHALL SPACE FLIGHT CENTER CONFIGURATION




GROUP XV




WIND VELOCITY EFFECTS AT 338°, LOW FLOWRATE

RUNS 34.1 and 34.2





$\beta = 338^\circ$

Low Flowrate





ORIGINAL PAGE IS
OF POOR QUALITY



\square -RUN32(2), V=6 KTS \circ -RUN34(1), V=7 KTS Δ -RUN34(2), V=20 KTS

MARSHALL SPACE FLIGHT CENTER CONFIGURATION




GROUP XVI

WIND VELOCITY EFFECTS AT 180°, LOW FLOWRATE




RUNS 35.1 and 35.2

$\beta = 180^\circ$




Low Flowrate



ORIGIN OF COORDINATES
OF POOR QUALITY



ORIGINAL PAGE IS
OF POOR QUALITY



□-RUN32(2), V=0 KTS ○-RUN35(1), V=7 KTS △-RUN35(2), V=20 KTS

MARSHALL SPACE FLIGHT CENTER CONFIGURATION

GROUP XVII




WIND VELOCITY EFFECTS AT 90°, LOW FLOWRATE



RUNS 36.1 and 36.2

$\beta = 90^\circ$

Low Flowrate

ORIGINAL PAGE 13
OF POOR QUALITY









MARSHALL SPACE FLIGHT CENTER CONFIGURATION
GROUP XVIII
WIND VELOCITY EFFECTS AT 90°, HIGH FLOWRATE
RUNS 37.1 and 37.2




$\beta = 90^\circ$




High Flowrate



ORIGINAL PAGE IS
OF POOR QUALITY










□-RUN32(1), V=0 KTS ○-RUN37(1), V=7 KTS △-RUN37(2), V=20 KTS

ORIGINAL PAGE IS
OF POOR QUALITY




MARSHALL SPACE FLIGHT CENTER CONFIGURATION
GROUP XIX
WIND VELOCITY EFFECTS AT 180°, HIGH FLOWRATE
RUNS 38.1 and 38.2




$\beta = 180^\circ$

High Flowrate



ORIGINAL PAGE IS
OF POOR QUALITY





\square -RUN32(1), $V=0$ KTS \circ -RUN30(1), $V=7$ KTS Δ -RUN30(2), $V=20$ KTS

ORIGINAL FIGURE
OF POOR QUALITY

MARSHALL SPACE FLIGHT CENTER CONFIGURATION





GROUP XX




WIND VELOCITY EFFECTS AT 338°, HIGH FLOWRATE

RUNS 39.1 and 39.2




$\beta = 338^\circ$

High Flowrate





ORIGINAL PAGE IS
OF POOR QUALITY



□-RUN32(1), V=0 KTS ○-RUN39(1), V=7 KTS △-RUN39(2), V=20 KTS

MARSHALL SPACE FLIGHT CENTER CONFIGURATION


GROUP XXI

WIND VELOCITY EFFECTS AT 0° , HIGH FLOWRATE



RUNS 40.1 and 40.2

$\beta = 0^\circ$




High Flowrate





ORIGINAL LOCATION
OF PRESSURE TAP



ORIGINAL PAGE IS
OF POOR QUALITY



ORIGINAL PAGE 10
OF POOR QUALITY



MARSHALL SPACE FLIGHT CENTER CONFIGURATION

GROUP XXII




FLOWRATE EFFECTS AT 7 KT

RUNS 34.1 and 39.1

$V = 7$ KNOTS




$\beta = 338^\circ$

ORIGINAL PAGE IS
OF POOR QUALITY






$\theta = 40 \text{ \& } 45$
 \square - RUN 34 (1), SMALL NOZZLE \circ - RUN 39 (1), LARGE NOZZLE $V = 7 \times 15$

ORIGINAL PAGE 13
OF POOR QUALITY



ORIGINAL PLOT
OF POOR QUALITY



□-RUN34(1), SMALL NOZZLE ○-RUN39(1), LARGE NOZZLE $V=7RTS$

MARSHALL SPACE FLIGHT CENTER CONFIGURATION

GROUP XXIII




FLOWRATE EFFECTS AT 20 KT




RUNS 34.2 and 39.2



$V = 20$ KNOTS

$\beta = 338^\circ$

ORIGINAL PAGE IS
OF POOR QUALITY















ORIGINAL PARTIAL
OF POOR QUALITY

MARSHALL SPACE FLIGHT CENTER CONFIGURATION
GROUP XXIV
WIND DIRECTION EFFECTS AT 7 KT, LOW FLOWRATE
RUNS 33.1, 36.1, 35.1 and 34.1




V = 7 KNOTS

Low Flowrate





ORIGINAL PAGE IS
OF POOR QUALITY



\square - RUN33(1), BETA=050
 \times - RUN34(1), BETA=330
 \circ - RUN36(1), BETA=090
 Δ - RUN35(1), BETA=180
 V=7KTS SMALL NOZZLE

C-2

MARSHALL SPACE FLIGHT CENTER CONFIGURATION




GROUP XXV




WIND DIRECTION EFFECTS AT 7 KT, HIGH FLOWRATE




RUNS 40.1, 37.1, 38.1 and 39.1

V = 7 KNOTS


High Flowrate







\square - RUN 40 (11), BETA = 000
 \circ - RUN 37 (11), BETA = 090
 Δ - RUN 38 (11), BETA = 180
 \times - RUN 39 (11), BETA = 330
 ∇ - 7XTS LARGE NOZZLE



MARSHALL SPACE FLIGHT CENTER CONFIGURATION




GROUP XXVI

WIND DIRECTION EFFECTS AT 20 KT, LOW FLOWRATE




RUNS 33.2, 36.2, 35.2 and 34.2




V = 20 KNOTS

Low Flowrate



ORIGINAL PAGE 13
OF POOR QUALITY





\square - RUN33(2), BETA=000 \circ - RUN36(2), BETA=090 Δ - RUN35(2), BETA=100
 \times - RUN34(2), BETA=330 V=20KTS SMALL NOZZLE

MARSHALL SPACE FLIGHT CENTER CONFIGURATION





GROUP XXVII

WIND DIRECTION EFFECTS AT 20 KT, HIGH FLOWRATE




RUNS 40.2, 37.2, 38.2 and 39.2



V = 20 KNOTS

High Flowrate



ORIGINAL PAGE IS
OF POOR QUALITY










MARSHALL SPACE FLIGHT CENTER CONFIGURATION




GROUP XXVIII



FLOWRATE EFFECTS, NO WIND

RUNS 32.1 and 32.2

V = 0 KNOTS








ORIGINAL PAGE IS
OF POOR QUALITY


HOT FILM DATA


MARSHALL SPACE FLIGHT CENTER CONFIGURATION

BASE PRESSURE DATA




X-R=156.56 \square -R=148.12 O-R=139.02 Δ -R=77.48 Σ -R=0






RUN33(1)

+ - R=156.56 x - R=148.12 \square - R=139.02 Δ - R=77.48 Σ - R=0




RUN33(2)

$+$ -R=156.56 x -R=148.12 \square -R=139.02 \triangle -R=77.48 Σ -R=0




RUN34(1)

Δ -R=156.56 \times -R=148.12 \square -R=139.02 \circ -R=105.09 Δ -R=77.48 \times -R=0




RUN34 (2)

$+-R=156.56$ $x-R=148.12$ $\square-R=139.02$ $\Delta-R=105.09$ $\Delta-R=77.48$ $\Sigma-R=0$




RUN35(11)

\square -R=148.12 \times -R=156.56 \circ -R=105.09 Δ -R=77.48 Σ -R=0




RUN35(2)

\square -R=148.12 \circ -R=105.09 \times -R=156.56 Δ -R=77.48




RUN36 (1)

+--R=156.56 x--R=148.12 □--R=139.02 O--R=105.09 Δ--R=77.48 X--R=0




RUN36 (2)

$\Delta-R=156.56$ $\times-R=148.12$ $\square-R=139.02$ $\circ-R=105.09$ $\Delta-R=77.48$ $\Sigma-R=0$




RUN37(1)

+ - R=156.56 x - R=148.12 □ - R=139.02 Δ - R=77.48




RUN37(2)

+ -R=156.56 x -R=148.12 □ -R=139.82 Δ -R=77.48 X -R=0




RUN38(1)

$+-R=156.56$ $\times-R=148.12$ $\square-R=139.02$ $\circ-R=105.09$ $\Delta-R=77.48$ $\times-R=0$




RUN38(2)

$+-R=155.56$ $\times-R=148.12$ $\square-R=139.02$ $\circ-R=105.09$ $\triangle-R=77.48$ $\Sigma-R=0$




RUN39(1)

$+$ -R=156.56 \times -R=148.12 \square -R=139.02 Δ -R=77.48 Σ -R=0




RUN39(2)

+R=156.56 X-R=148.12 □-R=139.02 O-R=105.09 Δ-R=77.48 X-R=0



RUN40(11)
 $+-R=156.56$ $\times-R=148.12$ $\square-R=139.02$ $\Delta-R=105.09$ $\Delta-R=77.48$ $\Sigma-R=0$



RUN40(2)


+ - R=156.56 X - R=148.12 □ - R=139.02 O - R=105.09 Δ - R=77.48 Σ - R=0

FEEDLINE AND CABLE TRAY



PRESSURE DATA


ALL CONFIGURATIONS

ALL RUNS





ORIGINAL PAGE IS
OF POOR QUALITY












ORIGINAL PAGE IS
 OF POOR QUALITY





ORIGINAL PAGE IS
OF POOR QUALITY













ORIGINAL PAGE IS
OF POOR QUALITY






ORIGINAL PAGE 13
OF POOR QUALITY




ORIGINAL PAGE 18
OF POOR QUALITY





ORIGINAL PAGE 13
OF POOR QUALITY











ORIGINAL PAGE IS
OF POOR QUALITY






ORIGINAL PAGE NO
OF POOR QUALITY






ORIGINAL PAGE IS
OF POOR QUALITY











ORIGINAL PAGE IS
OF POOR QUALITY






ORIGINAL PAGE
OF POOR QUALITY






ORIGINAL PAGE IS
OF POOR QUALITY





ORIGINAL FIGURE
OF POOR QUALITY







ORIGINAL PAGE 15
OF POOR QUALITY



ORIGINAL PAGE 13
OF POOR QUALITY



ORIGINAL PAGE IS
OF POOR QUALITY



HOT-FILM DATA

NOMINAL CONFIGURATION

WIND ONLY, JETS ONLY, WIND AND JET COMPARISONS


RUNS 19(c), 19(b), 19(a)

$P = 32$ psia N/A on 19(a)

$V = 20$ KNOTS N/A on 19(b)

$\phi = 0^\circ$

$\beta = 338^\circ$ N/A on 19(b)



NOMINAL CONFIGURATION

WIND EFFECTS


RUNS 19(b), 24

$P = 32$ psia

$V = 20$ KNOTS N/A on 19(b)

$\phi = 0^\circ$

$\beta = 112^\circ$ N/A on 19(b)



□-JETS ONLY (32psia) ○-WIND (Beta=112deg) and JETS

RUN 24

RUN 19(b)

NOMINAL CONFIGURATION

VELOCITY SURVEYS


RUN 23

$P = 32 \text{ psia}$

$V = 20 \text{ KNOTS}$


$\phi = 0^\circ$

$\beta = 338^\circ$



RUN23 Velocity Survey

\square - $X_T=793$ \circ - $X_T=514$



□ - θ = 0 ○ - θ = 45 △ - θ = -45
 × - θ = 135 + - θ = -135

RUN 23

MARSHALL SPACE FLIGHT CENTER CONFIGURATION

VELOCITY AND TEMPERATURE SURVEYS

RUN 41.2

$V = 20$ KNOTS


$\beta = 338^\circ$

High Flowrate


Nozzle Temp. = 197°F


Test Section Temp.

prior to test start - 75°F




□--RUN41(2) X_T=793 Temperature Survey





□-RUN41(2) $X_T=793$ Velocity Survey



MARSHALL SPACE FLIGHT CENTER CONFIGURATION

WIND VELOCITY EFFECTS

RUNS 42, 43


$\beta = 0^\circ$

High Flowrate


Nozzle Temp. = 197°F


Test Section Temp.

prior to test start = 75°F




□-RUN42 V=7KTS ○-RUN43 V=20KTS





CONFIGURATION: Nominal
WIND VELOCITY: run 42 -- 7
run 43 -- 20
High Flowrate

□-RUN42 V=7KTS O-RUN43 V=20KTS Δ-ET NOSE V=7KTS
X-ET NOSE V=20KTS



CONFIGURATION: Nominal
WIND VELOCITY: run 42 -- 7
run 43 -- 20

□-RUN42 V=7KTS ○-RUN43 V=20KTS

High Flowrate